

# EUROPEAN PATENT OFFICE

## Patent Abstracts of Japan

AID

PUBLICATION NUMBER : 04003482  
PUBLICATION DATE : 08-01-92


APPLICATION DATE : 20-04-90  
APPLICATION NUMBER : 02103196

APPLICANT : NIPPON TELEGR & TELEPH CORP  
<NTT>;

INVENTOR : KOMUKAI TETSUO;

INT.CL. : H01S 3/17 C03C 3/32 C03C 4/12  
G02B 6/00 G02B 6/16 G02F 1/00  
G02F 1/35 G02F 1/35 H01S 3/094

TITLE : FIBER LASER MEDIUM AND OPTICAL  
AMPLIFIER USING THE SAME



ABSTRACT : PURPOSE: To obtain the light of a  $1.3\mu\text{m}$  band with high efficiency, and to enable connection with a fiber for infrared light for optical communication in low coupling loss by using the fluoride glass fiber simultaneously containing specific quantities of Nb and Eu in a core section.

CONSTITUTION: The composition of a fiber laser medium is composed of  $\text{ZrF}_4=50\text{-}58\text{mol}\%$ ,  $\text{BaF}_2=33\text{-}36\text{mol}\%$ ,  $\text{LaF}_3=3\text{-}6\text{mol}\%$  and  $\text{AlF}_3=2\text{-}5\text{mol}\%$ , and both  $\text{NbF}_3$  and  $\text{EuF}_3$  are brought to  $1\text{mol}\%$  or less. The core diameter of the fluoride fiber is set at  $5.5\text{-}7.5\mu\text{m}$ , a clad diameter at  $125\mu\text{m}$  and a cutoff wavelength at  $0.78\text{-}0.80$ . Excitation light 4 input to a synthesizer 6 through an optical fiber 5 is brought to approximately 95% of intensity, where a laser medium 1 begins to oscillate, laser beams 2 as an optical signal are input to the synthesizer 6 through an optical fiber 3, and an optical signal amplified is taken out of the laser medium 1 coupled with the output end of the synthesizer.

COPYRIGHT: (C)1992,JPO&Japio

BEST AVAILABLE COPY